

Introduction

Professional:

- 20 degree CCD Camera
- 6 meter wheel base
- 8 toe sensors
- Fast radio data transfer

Time saving features:

- Standard measurement
- Fast measurement
- Additional measurement
- Lower car function
- Customer defined car data base

Reliable:

- Solid constructions of sensor heads
- Water protected
- Standard batteries
- Standard high quality PC
- Self centring clamps, optional adapters for Aluminium rims available

Affordable:

- Unbeatable price / performance ratio
- Designed for long time use

Specifications

| Item | Range |
|---------------------|-------|
| Front total toe-in | ±40° |
| Front toe-in | ±20° |
| Front camber | ±8.0° |
| Caster | ±20° |
| Kingpin inclination | ±20° |
| Rear total toe-in | ±40° |
| Rear toe-in | ±20° |
| Rear camber | ±8.0° |
| Thrust angle | ±5.0° |

Note: The above accuracy can be confirmed only when the user follows the procedures described by the operation manual.

Requirements on Surroundings

| | |
|---------------------|----------|
| Ambient temperature | -10~50°C |
| Relative humidity | ≤85% |

Features



Sensor head:

- Aluminium casting frame
- 20 degree toe CCD Camera
- Camber, Caster inclination sensor
- LCD Display
- Smart keys
- Replaceable without calibration



Programme:

- Standard
- Fast
- Additional
- Zoom function
- Lifted position adjustment
- Self check



Target Data:

- X-large car Database
- Customer Database
- Adjustment pictures

Accessories



Universal clamp
Aluminium Kit(optional)



Universal clamp



Quick clamp (optional)



Placement platform for probe
rods and wheel clamps (optional)



Mechanical turntables